



Features

- Fanless system with IBASE IB915 3.5" Single Board Computer
- Onboard 6th Gen Intel® Core™ U-series Processor
- iSMART- for auto-scheduler and power resume
- 12V (-10%) ~ 24V (+10%) DC wide-range power input
- Supports 1x Mini PCIe (full-size)
- Supports 1x 2.5" SATA HDD
- 1x USB 3.1 port (Type-C), 4x USB 3.0 ports
- Wall mount kit included

Specifications

System Mainboard	IB915AF-6600 / IB915AF-6300 / IB915AF-6100
CPU Type	Intel® Core™ i7 6600U Processor Intel® Core™ i5 6300U Processor Intel® Core™ i3 6100U Processor
System Speed	2.6GHz / 2.4GHz / 2.3GHz
Memory	2x 2GB DDR3L-1600 SO-DIMM Memory, Max. 16GB
Front Panel External I/O	1x power button 2x USB 2.0 1x Audio jack for Line-out / Line-in / Mic-in 1x HDD LED 1x Digital I/O (4-in / 4-out)
Rear Panel External I/O	1x COM thru RJ50 connector (RS-232/422/485) 3x COM (RS232) 4x USB 3.0 ports 1x USB 3.1 port (Type-C) 1x DisplayPort 2x RJ-45 GbE connector 1x 3-pin DC-in terminal block for 12V (-10%)~24V (+10%)
Expansion Slots	1x Full-size Mini PCIe socket
Storage	1x 2.5" HDD or SSD
Construction	Aluminum & Steel
Chassis Color	Black
Mounting Type	Desktop or wall mount (wall mount kit included) Optional VESA mount kit
Dimensions	180mm (W) x 150mm (D) x 66mm (H) 7.09" (W) x 5.91" (D) x 2.6" (H)
Weight	1.8 kg
Operating Temperature	0°C~40°C (32°F~104°F) (With HDD) -10°C~50°C (14°F~122°F) (With SSD)
Storage Temperature	-20°C ~ 80°C (-4°F~176°F)
Relative Humidity	5~90% @ 45°C, (non-condensing)
Vibration	Operating : 0.25Grms / 5~500Hz Non-operating : 1Grms / 5~500Hz
Shock	Operating : 20G / 11ms Non-operating : 40G / 11ms
Certification	CE / LVD / FCC Class B

Ordering Information

ASB200-915-i7M	Fanless chassis with IB915AF-6600, Intel® i7-6600U 2.6GHz CPU, 4x COM, supports iAMT11.0, w/o memory/ Storage/ 90W power adaptor and VESA mount bracket
ASB200-915-i5M	Fanless chassis with IB915AF-6300, Intel® i5-6300U 2.4GHz CPU, 4x COM, supports iAMT11.0, w/o memory/ Storage/ 90W power adaptor and VESA mount bracket
ASB200-915-i3M	Fanless chassis with IB915F-6100, Intel® i3-6100U 2.3GHz CPU, 4x COM, w/o memory/ Storage/ 90W power adaptor and VESA mount bracket
ASB200-915-i7-DCM	Fanless chassis with IB915AF-6600, Intel® i7-6600U 2.6GHz CPU, 4x COM, 1x90W power adaptor, supports iAMT11.0, w/o memory/ Storage/ VESA mount bracket
ASB200-915-i5-DCM	Fanless chassis with IB915AF-6300, Intel® i5-6300U 2.4GHz CPU, 4x COM, 1x 90W power adaptor, supports iAMT11.0, w/o memory/ Storage/ VESA mount bracket
ASB200-915-i3-DCM	Fanless chassis with IB915F-6100, Intel® i3-6100U 2.3GHz CPU, 4x COM, 1x 90W power adaptor, w/o memory/ Storage/ VESA mount bracket
90W power adaptor (optional)	90W (24V @3.75) power adaptor, DC-jack or bare wire type, Compatible with IEC62368-1/EN62368-1

Dimensions and Drawing

