



Features

- 10th Gen Intel® Xeon® W / Core™ i9/i7/i5/i3 / Pentium® Gold / Celeron® Processor with W480E or H420E PCH (CML-S)
- 2x DDR4 UDIMMs, Max. 64GB (ECC/ Non-ECC)
- 6x RJ45 GbE on board
- Optional NIC slot (only for INA3600W)
- 1x PCI-E (x8) expansion slot
- 300W power supply

Specifications

CPU	INA3600W: LGA1200 Socket for Intel® Xeon® W / Core™ i9/i7/i5/i3 / Pentium® Gold / Celeron® processor INA3600H: LGA1200 Socket for Intel® Core™ i9/i7/i5/i3 / Pentium® Gold / Celeron® processor
Chipset	INA3600W: Intel® W480E PCH chipset INA3600H: Intel® H420E PCH chipset
Memory	2x DDR4 UDIMMs Max. 64GB
Display	1x VGA 1x LCM
Ethernet	INA3600W: 6x Intel® I211-AT GbE on board Optional NIC module slot, Max. 8 LAN ports INA3600H: 6x Intel® I211-AT GbE on board
Bypass	2-Segments, LAN3/4 & 5/6
Expansion	1x PCI-E x16 slot (8-lane) for INA3600W
IPMI	N/A
Storage	3x 2.5" SATA drive bay (by SKU)
TPM	TPM 2.0
I/O	1x LCM (by SKU) 3x LED (Power/ HDD/ Status) 1x Reset button 1x RJ45 console 2x USB3.1
Power Supply	Full-range 300W power supply
Dimensions	438 (W) x 329 (D) x 44 (H) mm 17.24" (W) x 12.95" (D) x 1.73" (H)
Weight	9.0 kg (19.84 lbs)
Operating Temperature	0°C ~ 40°C (32°F ~ 104°F)
Storage Temperature	-20° ~ 70°C (-4°F ~ 158°F)
Operating Humidity	5 ~ 90%
Certification	CE/FCC

Dimensions

