



MPT-1000V VIDEO



Specifications

System Mainboard	MBT-1002V
CPU Type	Intel® Atom® x7-E3950 Processor Intel® Celeron® N3350 Processor
Processor Speed	1.6GHz, up to 2.0GHz
Memory	Onboard 4GB LPDDR4 memory (Intel® N3350 SKU) Onboard 8GB LPDDR4 memory (Intel® E3950 SKU)
Front panel I/O	1x DVI-D connector for display connection 1x VGA DSub15 2x RJ45 for GbE LAN 1x 3.5mm blue color audio connector for line input 1x 3.5mm pink color audio connector for MIC-Input 2x external accessible SIM socket (Coved) 1x external micro SD card slot (Coved together with SIM card holder) 1x Stack USB connector for 2x USB3.1 (#1/#2) 1x DUSB 9 for COM1 RS-232/485 1x DUB9 for COM2 RS-485 isolated 1x DSub15 for DIDO 6in/6out isolated 6x insulated DO: - Output type: Darlington transistor - Sink current •500 mA for one channel @100% duty - Source current •500 mA for one channel @100% duty cycle - Supply voltage: 5V-35V DC - Isolation voltage: 2500V RMS 6x insulated DI: - Maximum input range •24V, non-polarity - Digital logic levels •0~24 V, non-polarity - Input high voltage: 5V~24V - Input low voltage: 0~1.5V - Input resistance: 1.2 k @ 0.5W - Isolation voltage •2500V RMS 1x tack switch for system reset 1x tack switch for Add-on cards reset 1x tack switch for power firmware load default Indicators: - 1x Green color LED for power status - 1x White color LED for storage activity status - 1x Blue color LED for WLAN activity status (option) - 1x Orange color LED for WWAN activity status (option) - 1x Green color LED, programmable - 1x Red color LED for warning of wrong power voltage connected - 1x Blue color LED for external battery connected
Rear Panel External I/O	2x DSub9 for COM3/4 RS232 1x 4 pins terminal block for 2 masters CANbus 1x USB 3.0 flag type-A 1x Audio jack for line out 1x Tack switch for clear CMOS 1x Open window for accessing RTC battery 1x 6-pin ATX connector for external battery, and 19V DC(Max:1A) output 1x Blade fuse socket with cover 1x DIP switch for selecting power mode: CAR/DC 1x 3-pin terminal block for power input and IGN
Storage	1x 2.5" device bay for SSD/HDD 1x mSATA via mini-PCI-E slot

Features

- SIM socket supports Dual WWAN
- Removable 2.5" device bay
- Ignition power-on signal control
- Onboard CANbus
- Rich I/O interfaces for wireless, SSD, GPS, WWAN and add-on card expansion
- Add on card slots reset function
- Quick accessible RTC battery

Expansion slots	1x miniPCI-E full/Half-size, supports mSATA 1x miniPCI-E full/Half-size, supports second SIM card 1x M.2 B-key 30x42 with USB 2.0 and USB 3.0 signal only, supports first SIM card
Power Supply	9V~32V DC input(10%) without backup battery power 12V~32V DC input with backup battery Ignition detection: enable (Car mode)/ disable (DC mode) Reverse protection
Construction	Matel
Chassis Color	Black
Mounting	Side mounting, rack mounting with optional bracket
Dimensions	300 (W) x 158.4 (D) x 66 (H) mm 11.8" (W) x 6.23" (D) x 2.6" (H)
Operating Temperature	-40°C~70°C, with SSD, not including add-on cards (Intel® E3950 SKU) -5°C~50°C, with SSD, not including add-on cards (Intel® N3350 SKU)
Storage Temperature	-40°C~85°C (-40°F~185°F)
Relative Humidity	10 ~ 95% @ 45°C, (non-condensing)
Vibration	Operating/Non-operating: 2.26 Grms (5~500 Hz) / MIL-STD-810G composite wheeled condition (Z-axis only)
Shock	Non-operating: Sawtooth: 40G, 11 msec (Z-axis) Operating: Sawtooth: 20G, 11msec (Z-axis)
Certified	E-Mark, CE (EN 62368 / EN55032 / EN55025)/ FCC Class-A

Ordering Information

MPT-1000V8GM	Intel® E3950 processor, 8G LPDDR4 RAM onboard, 9V~32V DC input (12V~32VDC if connected with backup power), ignition detection, no OS, adaptor and storage
MPT-1000VNM	Intel® N3350 processor, 4G LPDDR4 RAM onboard, 9V~32V DC input (12V~32VDC if connected with backup power), ignition detection, no OS, adaptor and storage

Dimensions

